

CAT.5e UTP Patch Cord Yellow - 2MTR

Avalon Patch Cords have been designed for high speed data transmission over local area Networks (LANs) and for Gigabit Ethernet 1000Mbps applications. These cables exceed performance requirements specified by the TIA/EIA-568C.2,ISO/IEC 11801:2011 Edition 2.2 and CENELEC EN 50173(2011) for Category D applications. Avalon cables are ideal for simple, cost-effective and high-speed transmission performance. They support a higher Signal - to -noise ratio, providing better reliability for current applications and higher data rates for future applications. These Patch Cords comprise of a flexible patch cable and terminating with two modular plugs along with molded boots.

Make	AVALON
Туре	Patch Cord
Colour	Yellow
Pairs	4
Length	2 Meter

Applications

- Patch Work and Work Area
- 4/16 Mbps Token Ring(IEEE 802.5)
- 10/100/1000 Base (IEEE 802.3)
- 155Mbps ATM
- 100 Mbps TP-PMD
- Analogue Voice ,ISDN,ADSL

Specifications

- Insulation Material: HDPE
- Conductor and Metal: 7 Bare Copper Wires, 24 AWG
- Jacket: PVC, UL94V-0
- Plugs: RJ-45 8P8C
- Contact: Gold plated: 30U"
- Contact blade: Phosphor Bronze
- Molded Boot: Fire Retardant PVC
- Fire Resistant: CMG Specifications

Standards

- ISO/IEC11801:2011(Ed. 2.2)
- ANSI/TIA/EIA-568-C.2
- EN 50173-1:2011
- EN 50173-2:2007 including amendment A1:2010
- IEC61935-2:2010(Ed.3.0)
- ROHS Compliant

Ordering Information

Part No.	Description	Length	Colour
ANC5EUPYL-2MT	CAT.5e UTP Patch Cord - 2MTR	2 Meter*	Yellow*

^{*} Available in different lengths and colours.

