

24 Port SC Fiber Optic Patch Panel

Avalon 24 port Sliding Patch Panel is suitable for SC panel and can be ordered for ports such SC type. The panel can also be pre-loaded completely with the required adapter and simple management kit. The sliding system in its basic form can be supplied with or without adapters. The tray is locked in place and has two plastic catches for simple installation. When fully extended the tray is designed to lower at 45 degrees or move the tray to the side and locks at 10 degrees only. It fully provides a perfect working flat form for simple installation and easy maintenance.

Features

- Recessed Panel and Adapters option with better bend radius
- No exposed screws
- 45 degrees working angle
- Multifunctional rear cable entry options
- Panel and Rack number identification labels
- 4 Cable Entries (2XPG16, 2XPG13.5)



Applications

- Telecommunication networks
- FTTH
- LAN, WAN, CATV networks
- Active device termination

Specification

Element	24 Port
U Size	1U (44.4mm)
Width	483 mm
Depth	200 mm
Weight	2.8 Kg fully
Packaged Dimensions	450mm (W) X 55mm (H) x 260mm (D)
IP Rating	IP20
Adapter Options	SC
Number of ports	24
Cable Entry 20mm	2
Mounting adjustment range	50 mm
Material	Cold Rolled Steel
Material thickness	1.2 mm
Material coating	Powder coating
Colour	Black RAL 9004
Operating Temperature	- 40°C to + 50°C
Compliant to	RoHS, Reach / SVHC
Designed in accordance	TIA/EIA 568.C, ISO/IEC 11801, EN 50173, IEC 60304, IEC 61754, EN 297-1

Ordering Information

Part No.	Description
ANPP-24-1U-SC	24 Port Fiber Patch Panel with splice tray for SC Duplex Adaptors 19 inch Rack Mount - Unloaded