



16 Way PDU with 12 C13 Sockets and 4 C19 Sockets, 16A, 3mtr Cable with IEC60309 Plug

Main Function	Description		
Product series/product name	A: PDU series / Power Distribution Unit (Neutral)		
Installation method	Reversed installation / cable top (Rear Right)		
Mounting brackets	25 square hole flap (1 u); 25 nonporous baffle (1 u)	2-	
Power input method	16 A IEC60309 plug; 3 * 2.5 mm squared the power cord 【3M】 (Non RVV)		
Functional module	/		
Output Unit	C13 socket-1U【12】; C19 socket - 1 u【4】		
Housing Color	Black		
Product Size specifications	L x W x H = 760*44.4*44.4 (mm) ±2mm		
Fixed hole center distance	735 mm		
Profile length	710 mm		760 735 710
Cable fixing method	Line buckle (nylon)		
Product Identification			
Product name	Power Distribution Unit		
Rated voltage	220 - 250 v 50/60HZ		
Rated current	16 A		
Rated power	4000 W		
Safety certification	CE-EMC/CE-LVD/RoHS/UL94-V0/Glow Wire/Ball Pressure/CCC/ISO 9001 / Tyre Certification		
Identification	PDU		
Ordering Information			44.4
AN-16WPDU-12C13-4C19-16A	16 Way PDU with 12 C13 Sockets and 4 C19 Sockets , 16A, 3mtr cable with IEC60309 Plug		







