



24 Way PDU with C13 Sockets, 32A, 2x1P 16A Circuit Breaker, 3mtr cable with IEC60309 Plug

Main Function	Description
Product series/product name	A: PDU series / Power Distribution Unit (Neutral)
Installation method	Reversed Installation / Cable Top (Rear right)
Mounting brackets	- 70 round hole flap (1u); - 70 without baffle hole (1U)
Power input method	32A IEC60309 plug ; 3 * 6.0 mm squared the power cord 【3M】 (Non RVV)
Functional Module	1P type 16A EA9 open 【2】
Output Unit	C13 Locked Sockets-1U 【24】
Housing Color	Black
Product Size Specifications	L x W x H = 1581*44.4*44.4 (mm) ±2mm
Fixed Hole Center Distance	1541 mm
Profile Length	1441 mm
Cable Fixing Method	PG terminal (Normal)
Product Identification	
Product Name	Power Distribution Unit
Rated Voltage	220 – 250V 50/60HZ
Rated Current	32 A
Rated Power	8000 W
Safety Certification	CE-EMC/CE-LVD/RoHS/UL94-V0/Glow Wire/Ball Pressure/CCC/ISO 9001/ Tyre Certification
Identification	PDU
Ordering Information	
AN-24WPDUC13-32A	24 Way PDU C13 Sockets, 32A, 2x1P 16A circuit breaker, 3mtr cable with IEC60309 Plug

