

## 2 Pair, 22 AWG, PO, Individual Foil, LSZH - Audio, Control & Instrument Cable

### Product Description

Audio, Control & Instrument Cable, 22 AWG stranded (7x30) tinned copper conductors, polypropylene insulation, twisted pairs, individually foil shielded (100% coverage), 24 AWG stranded tinned copper drain wire, LSZH jacket.

### Technical Specifications

#### Product Overview

<b>Environmental Space:</b>	Indoor - Euro class DCA
<b>Suitable Applications:</b>	Instrumentation and computer cable; For data transmission applications



### Physical Characteristics (Overall):-

#### Conductor

AWG	Stranding	Material	No. of Pairs
22	7x30	TC - Tinned Copper	2

<b>Conductor Count:</b>	4
<b>Total Number of Pairs:</b>	2

#### Insulation

Material	Nominal Diameter	Diameter +/- Tolerance	Nominal Wall Thickness
PP - Polypropylene	1.17 mm	0.05 mm	0.009 in

### Color Chart

Number	Color
Pair 1	Black & Red
Pair 2	Green & White

### Inner Shield Material

Type	Material	Coverage [%]	Thickness of Foil	Drain wire Material	Drain Wire AWG	Drain wire Construction N x D
Tape	Aluminum / Polyester	100 %	9 / 12 μm	Tinned copper	AWG24/7	7x32

### Outer Shield Material

Material
Unshielded

### Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
LSZH / FRNC (UV stabilized)	4.55 mm	0.65 mm

### Construction and Dimensions:-

#### Stranding

Twists
8 twist/ft

### Electrical Characteristics

#### Conductor DCR

Individual Pair Nominal Shield DCR	Nominal Conductor DCR	Nominal Inner Shield DCR
15 Ohm/1000ft	49.2 Ohm/km	54.5 Ohm/km

#### Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
114.8 pF/m	203.4 pF/m

## Inductance

Nominal Inductance	Nominal Pair Inductance
0.17 $\mu$ H/ft	0.56 $\mu$ H/m

## Impedance

Nominal Characteristic Impedance
45 Ohm

## Delay

Max. Delay Skew	Nominal Velocity of Propagation (VP) [%]
66 ns/100m	66 %

## Current

Element	Max. Recommended Current [A]
Conductor	2.3 A

## Voltage

Voltage Rating [V]
300 V

## Temperature Range

Installation Temp Range:	-15°C To +80°C
Storage Temp Range:	-45°C To +80°C
Operating Temp Range (Flexible Install):	-15°C To +80°C
Operating Temp Range (Fixed Install):	-45°C To +80°C

## Mechanical Characteristics

Oil Resistance:	IEC 60811-404
Bulk Cable Weight:	24 lbs/1000ft
Max Recommended Pulling Tension:	226 N
Min Bend Radius During Installation:	45.5 mm
Min Bend Radius/Minor Axis:	2 in

## Standards

CPR Euro class:	Dca-s2,d1,a1
CENELEC Compliance:	EN 50290-2-27

## Applicable Environmental and Other Programs

EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
RoHS Compliant	Yes

## Suitability

Suitability - Indoor:	Yes
Suitability - Non-Halogenated:	Yes
Suitability - Sunlight Resistance:	Yes

## Flammability, LSOH, Toxicity Testing

ISO/IEC Flammability:	IEC 60332-1-2 and IEC 60332-3-24
Amount of Halogen acc. to IEC 60754-1 & EN50267-1:	Zero

## Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

## Ordering Information

Part Number	Description
AN2P-AV22BL-305MT-LSZH	2 Pair, 22 AWG, PO, Individual Foil, LSZH - Audio, Control & Instrument Cable