



2 Core, 16 AWG, Stranded BC Audio, Video, Security & Communication Cable, Shielded Cable



Product Description

2 Core, 16 AWG, Stranded BC Audio, Video, Security & Communication Cable, Shielded

Conductor	Material	Bare Copper wire
	Construction	19x0.29±0.005mm
	Nom. Dia.	1.45mm
	Size	16AWG
Insulation	Material	Polypropylene - PP
	Nom. OD	1.85±0.05mm
	Ave. Wall Thickness	0.20mm
	Color codes	Black & Red
	Make up	2 Cores twisted
Drain Wire	Material	Tinned Copper wire
	Construction	7x0.20±0.005mm
	Size	24 AWG
Shielding	Material	AL/pet foil, 100% coverage, AL side inward
Rip Cord	Material	Stranded rip cord
Jacket	Material	Grey PVC, RAL7000
	Nom. O.D.	4.80±0.20mm
	Nom. Wall Thickness	0.50±0.05mm
	Appearance	Extruded tube jacket, Ropy finish
Electrical Performance	Voltage Rating	300 Volt, Max
	Conductor DCR (20°C)	14.4 Ω / Km
Operating Temp.	- 20 °C to +60 °C	

Ordering Information

Part Number	Description
AN5200FE-305MT	2 Core, 16 AWG, Stranded BC Audio, Video, Security & Communication Cable, Shielded 305m Cable